



# GL501MG



LTE Cat M1/NB1 waterproof GNSS tracker supporting BLE 4.2 with up to 1 year standby time

150g (5.29oz) | 170g (6.0oz) (magnet-mounted version)

87 x 51 x 30mm | 3.43"(L) x 2.01"(W) x 1.18"(H) | 87 x 51 x 33.5mm | 3.43"(L) x 2.01"(W) x 1.32"(H) (magnetic case mounting version) | Li-Polymer 3.7V/2400 mAh

-20°C ~ +60°C

### Standby Time:

1 Report/ Day 1 Year

The GL501MG is an updated version of our successful GL500MG adding Qi wireless charging and BLE. Our customers love the battery-powered GL500MG but still wanted a rechargeable version for certain scenarios. We designed this version without impacting the waterproof and robust enclosure. Adding BLE allows connectivity to diverse wireless accessories. With internal temperature and light sensors, the product is ideal for a wide range of environmental monitoring applications such as cold chain logistics, warehouse management, cargo trucking, high-value static asset monitoring and more. The GL501MG supports several mounting alternatives which use unique clip on design to securely attach the device to any asset.



Lot Management



Asset Monitoring



Pharmaceutical Transportation

- Rapid & Covert Installation
- 1 Year Standby Time
- BLE 4.2
- Supports Wireless Charging
- OTA Control
- Scheduled Timing Report
- Geo-fences
- IP67 Waterproof
- Vibration Feedback
- Low Power Alarm
- Wakeup Report
- Motion Detection
- Automatic Mode Switching
- Temperature Monitoring
- Tamper Detection
- Magnetic mounting (Optional)
- Use with Animal Collars

**GL501MG**

Region	Network/Operating Band	GNSS Type	Position Accuracy (CEP)	Certificate
Worldwide	LTE Cat M1/NB1: LTE FDD: B1/B2/B3/B4/B5/B8/B12/B13/B18/ B19/B20/B25/B28 EGPRS: 850/900/1800/1900 MHz	u-blox All-in-One GNSS receiver	Autonomous: < 2.5m	CE/FCC/Verizon

**Appearance****Interfaces**

Power Button	Used for power on/off and working status checking
LTE Antenna	Internal only
GNSS Antenna	Internal only
BLE Antenna	Internal only
LED Indicators	GNSS, Battery charging and discharging status

**Air Interface Protocol**

Command Set	@Track protocol command
Transmit Protocol	TCP, UDP, SMS
Working Modes	Power saving mode for long standby time Continuous mode for emergency tracking
Scheduled Timing Report	Report position and status at preset time intervals
Geo-fences	Support up to 20 internal geo-fence regions
Low Power Alarm	Alarm when internal battery is low
Wakeup Report	Report when the device wakes up
Motion Detection	Motion detection based on internal 3-axis accelerometer
Reporting Frequency Adjustment	Intelligent adjustment of reporting frequency

## Accessories



### WTH300

BLE temperature and humidity sensor



### WKF300

BLE key fob for continuously detecting the on-board status of the device



### WBC300

BLE I/O expander used for engine control and locking control together with external relay



### Wireless Charger Accessories Kit\_US

This Kit includes the Type-C USB cable, USB charger and wireless charger. It's used for device charging

Parts list:

GL501\_Type-C USB calbe

Cable length: 100mm; Color: white

GL501MG\_USB charger For US

Model: RCL-U050100C

AC:100-240V; DC:5V-1A; Color: white

GL501MG\_Wireless charger


Model: RCL-WXC5WF

Input: 5W-1A; Output: 5V-800~1000mA



### GL500M Magnetic Mounting Bracket

It's used for mounting GL500 and GL501 LTE series



### GL500M Mounting Bracket

It's used for mounting GL500 and GL501 LTE series